# Oslo



### **SPECIFICATIONS**

Plank size Length: 1860 mm

Width: 190 mm

Thickness: 15(3.5) mm

Box Min 4 planks of 1.86 m

 $2.12 \text{ m}^2$ 

20 kg

Pallet 40 boxes Structure 3-layer

Coating Uv oil (aslo available unfinished)

Texture Slightly brushed

Standard colour White Oil, Nordic Oil, Atlantic Oil, Natural Oil, Paris White,

Azur Grey and unfinished

Grading BC

Top layer type Dry sawn veneer

Top layer thickness 3.5 mm

Bevel V-groove on the long side

Gloss  $10 \pm 5\%$ 

Locking system Tongue and groove

Type of installation Advised: glued or floating

### **STRUCTURE**

## **INSTALLATION**





### **PRODUCT CHARACTERISTICS - General**

Factor Standard - EN 14342

Density  $650 \text{ kg/m}^3$ , 15 mm

Fire resistance Dfl-S1
Formaldehyde emission E1

PCP  $\leq$  5 ppm Thermal conductivity 0.12 W/mK Biological durability Class 1

Surface soundness  $\geq 1.00 \text{ N/mm}^2$ 

Impact resistance EC0
Moisture level 5-10 %

Floor heating Allowed, according to specific standards